



**SPECIFICATIONS**

Current rating : 5~8.5A AC, DC  
 Voltage rating : 250V AC, DC  
 Temperature range : -45°C ~ +105°C  
 Contact resistance : 10mΩ Max  
 Insulation resistance : 1000MΩ Min  
 Withstanding voltage : 1500 V AC/minute  
 Contact Material : Brass  
 Finished : Tin-plated  
 Housing Material : LCP UL94-V0  
 Color : Black

PART NO:	Dimension mm	
	A	B
C3030WT-F-2*1P		6.65
C3030WT-F-2*2P	3.00	9.65
C3030WT-F-2*3P	6.00	12.65
C3030WT-F-2*4P	9.00	15.65
C3030WT-F-2*5P	12.00	18.65
C3030WT-F-2*6P	15.00	21.65
C3030WT-F-2*7P	18.00	24.65
C3030WT-F-2*8P	21.00	27.65
C3030WT-F-2*9P	24.00	30.65
C3030WT-F-2*10P	27.00	33.65
C3030WT-F-2*11P	30.00	36.65
C3030WT-F-2*12P	33.00	39.65

TOLERANCE	
X.	--
X.X	±0.25
X.XX	±0.20
X.XXX	±0.05
ANGULAR	--

**深圳市连欣科技有限公司**

TITLE  
3.0MM Pitch Wire to Board Header

APPROVALS	
DRAWN	Frank 16-July-2010
CHECKED	Denise 16-July-2010
APPROVED	Jessica 16-July-2010

VIEW	SCALE	PART NO.	REV.
	3:1	XDFW-C3030WT-***P	A2
UNIT	SIZE	DWG NO.	SHEET
MM	A4	C3030WT-005	1 OF 1